

Metalcraft's Metal Mount RFID Asset Tag is ideal for tracking fixed or mobile assets that have a metal surface and require attachment directly to the surface of the asset. The inlay is completely encapsulated within the label sealing it from environmental conditions that could have an adverse effect on the performance and life of the RFID tag. A 3/16" foam adhesive acts as a standoff allowing the RFID tag to read with minimum RF interference.

All Metalcraft RFID tags are designed with our proven durability, ready to withstand repeated usage in rugged environments, generating a greater ROI for your business. Each tag can be programmed to match the variable information printed on the label. Every product features a subsurface digital printing process which ensures crisp details on even the most complex logos for maximum clarity. Four color processing is available for limitless color and design options.

Key Product Features

- Ideal for asset tracking on metal surfaces
- Made of flexible polypropylene or polyester material
- Digital printing process provides for greater print capability with detailed logos or special designs
- Choice of up to four standard or custom colors
- Read range 5 to 6ft* mounted to metal surface

*Read range differs by environment and type of reader used

Not sure what product you need?

Call our trained Experts!

800-437-5283



149 4th Street SW • P.O. Box 1468
Mason City, IA 50401-1468
www.idplate.com
E-mail: metalcraft@idplate.com



Metal Mount RFID Tag Specifications

Material: .002” polypropylene or polyester: .20” total product thickness

Label Copy: The label copy may include block type, stylized type, logos or other designs. All copy, block type, stylized type, logos, designs, and bar code are subsurface printed. This unique process provides excellent resistance to solvents, caustics, acids and moderate abrasion.

Colors: Standard colors include black, red, yellow, green and blue. Due to contrast needed for the bar code scanner, all bar codes are black.

Serialization: Bar code and human-readable equivalent is produced using the latest high-resolution digital technology available, which provides excellent clarity and easy scanning. Code 39 is the standard symbology with a range of 2.7 to 9.4 CPI (characters per inch). Optional symbology is Code 128.

The bar code and human readable can be programmed into the RFID inlay as long as the information is in decimal or hexadecimal format. The programmed information can be locked, which prevents the RFID inlay from being rewritten. Metalcraft can encode up to 24 characters into the RFID inlay. If desired, Metalcraft can encode information that differs from the bar code and human readable.

Standard Sizes: No. 1126: 3.80 x 3.80”, No. 917: 4.5 x 1”

Shipment: 15 work days

To Order: Call **1-800-437-5283** and ask for an ID Specialist

Test Results

These tests were conducted for a limited period of time in strict laboratory conditions. In order to achieve maximum satisfaction we highly recommend that any customer considering use of this product test the labels in the environment in which they will be used.

Read Range Test: TagTag has a read range of 5-6* ft using Motorola AR400 reader at 30 dbm

Chemical Soak Test Results (24 hours): Test of label structure and printed image as well as readability of inlay.

Test Conditions	Result
Water	N.E.
Glass Cleaner	N.E.
Bathroom Cleaner	N.E.
Alcohol	Partially delaminated, Inlay Unreadable
Acetone	Delaminated, Inlay Unreadable
NaOH	N.E.
Nitric Acid	N.E.

* Read range differs by environment and type of reader usage



149 4th Street SW • P.O. Box 1468
Mason City, IA 50401-1468
www.idplate.com
E-mail: metalcraft@idplate.com