

Permanent Paint Resist Polymer Labels



These unique labels feature a special fluoropolymer laminate very similar to Teflon® coating in that it resists multiple paint applications (approximately 10-12), grease, even graffiti, and can withstand temperatures up to 250°F.

After painting, customers simply pick off the paint and are left with a clean, easy-to-scan polyester bar code label. Subsurface printing protects the logos, copy and bar code against extreme solvents, caustics, acids and moderate abrasion.

Features

Permanent paint-mask fluoropolymer laminate that is designed to resist multiple paintings (approximately 10-12) and can withstand temperatures up to 250°F
Conforms to uneven or curved surfaces
Subsurface printing protects against extreme solvents, caustics, acids and moderate abrasion
Digital printing process ensures bar code readability as well as crisp, clean company logos
Custom colors available at no additional charge

Product Print Options

Barcode . Data Matrix . QR Code . Serial Number . Text

Product Functionality

Abrasion Resistance . Chemical Resistance . Heat Resistance

Popular Applications

Restoration . Transportation / Logistics . Manufacturing

Category

Plastic Asset Tags

Permanent Paint Resist Polymer Labels

Specifications Data

Material	.002" thick polyester; available in white or silver.
Bar Code & Serialization	Bar code and human-readable equivalent is produced using the latest high-resolution digital technology available, which provides excellent clarity and easy scanning. Code 39 is the standard symbology with a range of 2.7 to 9.4 CPI (characters per inch). Optional symbologies include Code 128, I 2 of 5 and 2D DataMatrix.
Label Copy	The label copy may include block type, stylized type, logos or other designs
Colors	Standard colors include black, red, yellow, green, dark blue, orange, purple or blue. Custom spot colors are also available at no additional charge. Due to contrast needed for the bar code scanner, all bar codes are black.
Standard Adhesive	.002" thick pressure-sensitive adhesive. Adheres to uneven surfaces and even to slightly oily surfaces.
Sizes	1.75" x .625"; 2" x .75"
Packaging	Shipped on convenient rolls for ease of removal. Cleaning solution is provided to assist in applying to a clean surface. Cartons are clearly marked to indicate serial numbers of labels.
Shipment	6 business days



2019 Metalcraft, Inc.
3360 9th St SW Mason City, IA 50401
www.idplate.com |
www.universalrfid.com
Ph: 641-423-9460

