



Make it easy on yourself with easy-to-mark, easy-to-track Bar Code Cable Labels from Metalcraft. This product simplifies the task of marking cables, hoses, tubing, etc., by providing subsurface printing on one end with the clear part of the label wrapping around the pre-imaged information to provide additional protection. The propylene construction allows the label to conform to a tight radius without unwinding. The .002" thick adhesive provides excellent adhesion to hard-to-adhere-to plastic surfaces.

Metalcraft's digital subsurface printing allows for optimal clarity of detailed design and protection against solvents, caustics, acids and mild abrasion while eliminating the need for laminating. An onsite printing option is also available.

## Features

Subsurface printing protects against mild to moderate solvents, caustics, acids and mild abrasion while eliminating need for a laminate  
Polypropylene construction allows the label to conform to a tight radius without unwinding  
Clear part of label wraps around pre-imaged information for additional protection  
Digital printing process ensures bar code readability as well as crisp, clean company logos.

## Product Print Options

Barcode . Data Matrix . QR Code .  
Serial Number . Text

## Product Functionality

Abrasion Resistance . Chemical Resistance . Heat Resistance

## Popular Applications

Audio / Visual . IT Assets

## Category

Plastic Asset Tags

## Specifications Data

<b>Material</b>	<b>.002" thick clear polypropylene</b>
Bar Code & Serialization	Barcode and human-readable equivalent is digitally printed – providing excellent clarity and easy scanning. Code 39 is the standard symbology with a range of 2.7 to 9.4 CPI (characters per inch). Optional linear and 2D symbologies available. Although this product is primarily marketed as a bar code product, we can produce it with human-readable numbers only or unserialized.
Label Copy	The label copy may include block type, stylized type, logos or other designs
Colors	Standard colors include black, red, yellow, green, blue, orange, purple, dark blue. Custom spot colors are also available at no additional charge. Due to contrast needed for the bar code scanner, all bar codes are black.
Standard Adhesive	.002" thick low surface energy, pressure-sensitive adhesive. This adhesive provides excellent adhesion to plastic surfaces, uneven surfaces and even slightly oily surfaces.
Sizes	2.125" x 5"; 2" x 11"
Packaging	Shipped on convenient rolls with scrap matrix removed for ease of removal. Cartons are clearly marked to indicate serial numbers of labels.
Shipment	6 business days

## Chemical Testing

### Chemical Test Data


## Temperature Testing

Bar Code Cable Labels are able to withstand intermittent heat exposure to 250°F.

## Barcode Readability Testing

This rating measures bar code readability after being exposed to chemicals listed below for a 2 hour soak and a 24 hour soak.

### Barcode Readability Test Data

Test Conditions	2-hour soak	24-hour soak
Water	no effect	no effect
Glass cleaner	no effect	no effect
Bathroom cleaner	no effect	no effect
Alcohol	no effect	no effect
Acetone	no effect	no effect
Sodium hydroxide	no effect	no effect

## Label Adhesion Testing

This rating measures label adhesion after being exposed to chemicals listed below for a 2 hour soak and a 24 hour soak.

### Label Adhesion Test Data

Test Conditions	2-hour soak	24-hour soak
Water	no effect	no effect
Glass cleaner	no effect	no effect
Bathroom cleaner	no effect	adhesive softened
Alcohol	no effect	no effect
Acetone	no effect	no effect
Sodium hydroxide	no effect	no effect
Nitric acid	no effect	adhesive softened