

RFID Parking Permit Hang Tags



Like the RFID Windshield Tag, the Rearview Mirror Tag is an optimal choice for access control in parking lots, gated communities and anywhere vehicles come and go. The logo and bar codes are subsurface printed on thick polyester for durability and rigidity. Perfect for temporary access control applications when you need to avoid permanent attachment to the windshield. Completely removable and reusable.

Double-sided registered option is now available, too! Print a registered company logo or instructional information on the second side. You can even print the same variable number or bar code on both sides allowing anyone to see the information from either side of the tag.

Features

Specialized inlays read well through windshield glass
Unlimited color options with choice of up to four standard or custom colors
Digital printing process provides for greater print capability with detailed logos or special designs
Double-sided registered option available
High frequency (HF) RFID Tags available

Product Print Options

Barcode . Data Matrix . QR Code . RFID . Serial Number . Text

Product Functionality

Abrasion Resistance . Chemical Resistance . Heat Resistance . UV/Outdoor Durability

Popular Applications

Government . Museum . Transportation / Logistics . Construction / Tool Tracking . Hospitals . Schools

Category

Access Control . RFID Access Control . RFID Tags

RFID Parking Permit Hang Tags

Specifications Data

Material Polyester

Serialization Bar code and human-readable equivalent is produced using the latest high-resolution digital technology available, which provides excellent clarity and easy scanning. Code 39 is the standard symbology with a range of 2.7 to 9.4 CPI (characters per inch). Optional symbologies are available. The bar code and human readable can be programmed into the RFID inlay as long as the information is in decimal or hexadecimal format. The programmed information can be locked, which prevents the RFID inlay from being rewritten. Metalcraft can encode up to 24 characters into the RFID inlay. If desired, Metalcraft can encode information that differs from the bar code and human readable.

Label Copy The label copy may include block type, stylized type, logos or other designs

Colors Standard colors include black, red, yellow, green, dark blue, orange, purple or blue. Custom spot colors are also available at no additional charge. Due to contrast needed for the bar code scanner, all bar codes are black.

Standard Adhesive Hanging tag

Frequency Range UHF = 860-960 MHz; HF = 13.56 MHz

Sizes 6" x 2.25"; 4.175" x 2.55"

Packaging Shipped in "work-out-of" cartons for convenient application.

Shipment 14 business days

Chemical Testing

Test of label structure and printed image as well as readability of inlay.

Chemical Test Data

Test conditions (24-hour soak)	Result
Water	no effect
Glass cleaner	no effect
Bathroom cleaner	no effect
Alcohol	no effect
Acetone	Delaminated, inlay unreadable
NaOH	no effect
Nitric acid	no effect

Read Range Testing

Tag has a read range of 20+ ft using Motorola AR400 portal reader at 24 dbm